

XD5-12kW

Three Phase Hybrid Inverter



 Efficient Higher Revenue

- 160% DC input oversizing, Max. PV input current 20A
- Max. charge/discharge current 50A
- 110% output power oversizing, 200% peak output power

 Intelligent Simple O&M

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- IP66 protection: support outdoor installation
- DC & AC type II SPD: prevent lightning damage

 Flexible Abundant Configuration

- Plug & play, EPS switching under 10ms
- AFCI function (optional): when an arc-fault is detected the inverter immediately stops operation
- Multiple working modes

	XD5KTR	XD6KTR	XD8KTR	XD10KTR	XD12KTR
Input (PV)					
Max. Input Power	8kW	9.6kW	12.8kW	16kW	19.2kW
Max. Input Voltage		1100V			
Start-up Voltage		160V			
Rated Voltage		600V			
MPPT Voltage Range		150V~1000V			
Number of MPP Trackers	2				
Number of String per MPPT		1 / 1			
Max. Current per MPPT		20A			
Max. Short Circuit Current per MPPT		40A			
Output (AC)					
Rated Output Power	5kVA	6kVA	8kVA	10kVA	12kVA
Max. Output Power	5.5kVA	6.6kVA	8.8kVA	11kVA	13.2kVA
Max. Output Current	7.2A	8.7A	11.6A	14.5A	17.4A
Rated Grid Voltage		230Vac / 400Vac			
Rated Grid Frequency		50Hz / 60Hz			
THDi(@Rated Power)		< 2%			
Power Factor		0.8 leading ~ 0.8 lagging			
Output (EPS)					
Max. Output Power	5.5kVA	6.6kVA	8.8kVA	11kVA	13.2kVA
Peak Output Power, Time	10kW, 60s	12kW, 60s	16kW, 60s	20kW, 60s	20kW, 60s
Rated Voltage, Frequency		230V / 400V, 50Hz			
THDv(@Rated Power)		< 3%			
Switch Time		< 10ms			
Battery					
Battery Type		Lithium / Lead-acid			
Battery Voltage Range		160V ~ 800V			
Max. Charge / Discharge Current		50A			
Communication		CAN / RS485			
Efficiency					
Max. Efficiency		98.20%			98.40%
European Efficiency		97.60%			97.80%
Battery Charge / Discharge Efficiency		97.60%			97.80%
Protection					
DC Switch		Yes			
DC Reverse Polarity Protection		Yes			
Anti-islanding Protection		Yes			
AC Short Circuit Protection		Yes			
Residual Current Monitoring		Yes			
Insulation Resistance Monitoring		Yes			
Ground Fault Monitoring		Yes			
Over Current / Voltage Protection		Yes			
I-V Curve Scan		Yes			
Battery Soft Start Protection		Yes			
Surge Protection		Type II			
AFCI Protection		Optional			
Communication					
Display		LCD			
Communication		RS485 / CAN / WIFI / 4G / LAN / Bluetooth			
General Data					
Dimension (W x H x D)		534 x 440 x 220 mm			
Weight		<30kg			
Operating Temperature Range		-30°C ~ +60°C			
Cooling Method		Natural			
Protection Degree		IP66			
Max. Operating Altitude		4000 m			
Noise		< 35dB			
Relative Humidity		0~100%			
Self-consumption		< 10W			
Topology		Transformerless			

 INVT Solar



Sales E-mail: solar@invnt.com.cn Service E-mail: solar-service@invnt.com.cn Website: www.invnt-solar.com